



NYLON DOUBLE BRAIDS

Spliceable braided Nylon sleeve over a braided Nylon core. This rope meets all requirements of the U.S. Military specification MIL-R-24050-D. Due to its high strength and elongation, Nylon is the ideal choice where shock absorbancy is required.

Please contact us for Trade Pricing and Discounts

Packaging	Colors Available
600 Ft. Reel Bulk Box Special Lengths	White
	Black
	Red
	Blue
	Green
	Gold
	Brown
	Burgundy
	Purple

DIA.	CIRC.	AVG TENSILE STRENGTH	APPROX. WT. PER 100 FT.
1/4"	3/4"	2,300 lbs.	1.7 lbs.
5/16"	1"	3,400	2.7
3/8"	1-1/8"	4,900	3.7
7/16"	1-1/4"	6,500	5.0
1/2"	1-1/2"	8,500	6.5
9/16"	1-3/4"	11,000	8.4
5/8"	2"	15,000	11.7
3/4"	2-1/4"	19,000	15.0
7/8"	2-3/4"	27,500	21.5
1"	3"	33,000	26.0
1-1/8"	3-1/2"	44,000	35.0
1-1/4"	3-3/4"	50,000	40.0

COLOR BAR CHART

Actual Colors May Vary



CHARACTERISTICS NYLON DOUBLE BRAID	
Specific Gravity	1.14
Elongation at Break	30-35%
Critical Temp.	300°F
Abrasion	Excellent
UV Resistance	Good



Pelican Rope Works

The Finest Braided Ropes - Made Anywhere

1-800-464-7673

www.pelicanrope.com



Schedule
Contract GS-03F-0019T



4001 W. Carriage Drive • Santa Ana, CA 92704