



12-Strand Single-Braided KEVLAR®

This aramid fiber rope has more strength pound- for-pound than steel. A 100% KEVLAR 12-Strand SINGLE BRAIDED rope that offers advantages over steel wire rope. Low stretch, high strength and easy to splice. Not recommended for use over pulleys or flexing applications.

Please contact us for Trade Pricing and Discounts

Packaging	Colors Available
600 Ft. Reel Bulk Box Special Lengths	Yellow

DIA.	CIRC.	AVG TENSILE STRENGTH (lbs.)	APPROX. WT. (lbs. per 100 ft)
1/8"	3/8"	1,500 lbs.	0.65 lbs.
3/16"	9/16"	3,600	1.20
1/4"	3/4"	6,600	2.00
5/16"	1"	9,500	3.00
3/8"	1-1/8"	12,000	4.00
7/16"	1-1/4"	15,000	5.00
1/2"	1-1/2"	22,000	7.75
5/8"	2"	36,000	14.00
3/4"	2-1/4"	49,000	19.30
7/8"	2-3/4"	60,000	23.60
1"	3"	78,000	30.70

CHARACTERISTICS - 12-Strand Single-Braided KEVLAR	
Specific Gravity	1.44
Elongation at Break	1.5-4.5%
Critical Temp.	400°F
Abrasion	Fair
UV Resistance	Fair



Pelican Rope Works

The Finest Braided Ropes - Made Anywhere

1-800-464-7673

www.pelicanrope.com



Schedule
Contract GS-03F-0019T



4001 W. Carriage Drive • Santa Ana, CA 92704