



# Premium VLS™ Polyester DOUBLE BRAIDS

Pelican VLS™ braid (Very Low Stretch) is the result of design technology combining low-stretch, high strength and chafe resistance into one rope. Pelican VLS™ conforms to U.S. Mil spec MIL-R-24677 and is also available with a urethane coating to enhance identification and abrasion protection.

*Please contact us for Trade Pricing and Discounts*

DIA.	CIRC.	AVG TENSILE STRENGTH	APPROX. WT. lbs./100'
3/16"	9/16"	1,200 lbs.	1.3
1/4"	3/4"	2,200	2.3
5/16"	1"	3,300	3.2
3/8"	1-1/8"	4,400	4.4
7/16"	1-1/8"	5,800	6.2
1/2"	1-1/2"	8,200	8.0
9/16"	1-3/4"	11,000	10.1
5/8"	2"	13,500	12.3

Packaging	Colors Available
600 Ft. Reel Bulk Box Special Lengths	White
	Black
	Blue
	Red
	Green

CHARACTERISTICS - VLS Polyester Double	
Specific Gravity	1.38
Elongation at Break	15-20%
Critical Temp.	350°F
Abrasion	Excellent
UV Resistance	Excellent

## COLOR BAR CHART

*Actual Colors May Vary*



**Pelican Rope Works**

The Finest Braided Ropes - Made Anywhere

**1-800-464-7673**

www.pelicanrope.com



Schedule  
Contract GS-03F-0019T



4001 W. Carriage Drive • Santa Ana, CA 92704