



Standard Polyester

DOUBLE BRAIDS

Combines low stretch, high strength and chafe resistance into one rope.

Conforms to U.S. MIL Spec MIL-R-24677 and is also available with a urethane coating to enhance abrasion protection and longer life.

Please contact us for Trade Pricing and Discounts

DIA.	CIRC.	AVG TENSILE STRENGTH	APPROX. WT. lbs/100'
3/16"	9/16"	1,200 lbs.	1.3
1/4"	3/4"	2,200	2.3
5/16"	1"	3,300	3.2
3/8"	1-1/8"	4,400	4.4
7/16"	1-1/4"	5,800	6.2
1/2"	1-1/2"	8,200	8.0
9/16"	1-3/4"	11,000	10.1
5/8"	2"	13,500	12.3
3/4"	2-1/4"	19,000	18.1
7/8"	2-3/4"	27,600	23.5
1"	3"	36,700	32.0
1-1/8"	3-1/2"	45,000	42.0
1-1/4"	3-3/4"	54,000	50.0

Packaging	Colors Available
600 Ft. Reel Bulk Box Special Lengths	White Other Colors Special Inquiry

CHARACTERISTICS Std. Polyester Double Braid	
Specific Gravity	1.38
Elongation at Break	15-20%
Critical Temp.	350°F
Abrasion	Excellent
UV Resistance	Excellent



Pelican Rope Works

The Finest Braided Ropes - Made Anywhere

1-800-464-7673

www.pelicanrope.com



Schedule
Contract GS-03F-0019T



4001 W. Carriage Drive • Santa Ana, CA 92704